

LIME **SLURRY**

for a Textured Finish on Brick, Stone and Other Masonry



PRODUCT FEATURES

- Authentic, breathable, Italian lime paint used for beautiful, textured finishes in just 2 easy coats
- No primer needed on absorbent, unpainted, unsealed natural masonry surfaces
- Unique formulation allows Romabio Lime Slurry to harden like plaster
- For interior and exterior masonry surfaces
- Naturally mold-resistant and stands up to extreme temperatures
- No odor, Zero VOC and environmentally friendly

"At Highland Painting, we use Romabio products almost exclusively for their beauty and durability. Lime Slurry is our favorite textured masonry paint. With an almost endless open time and ease of application, it allows our team to transform basic brick structures into beautiful homes with a sophisticated European flare."

~ Ever Morales of Highland Painting, Dallas/Ft Worth



LIME **SLURRY**

for a Textured Finish on Brick, Stone and Other Masonry

COLOR PROFILE & BASE TYPE

- Romabio offers seven curated whites and neutrals in the Classico Color Collection including Avorio White (neutral, offwhite), Bianco White (pure, cool tone white), Cristallo White (antique, off-white), Nube Gray (subtle, beige-gray), Riposo Beige (light beige), Toscano Beige (soft beige), and Tropea Beige (true beige)
- Offered in White Base only that can be custom tinted light to medium-light colors
- For darker colors, finish with Romabio Masonry Flat, tinted to any color NO primer needed!
- Once dry, finish will be lighter and more opaque

SIZES AVAILABLE

2.5L SKU: LSL-UNTINT-WB-2.5L
 15L SKU: LSL-UNTINT-WB-15L

COVERAGE

- 2.5L/.67 gal. approximately 90-100 sq/ft*
- 15L/4 gal. approximately 540-600 sq/ft*

RECOMMENDED DILUTION** 2.5L/.67GAL 15L/4GAL 5% 125mL 750mL

APPLICATION ON MASONRY

- 1 Dampen the surface to be painted and keep damp as needed, especially in high heat
- 2 Apply with a Romabio Masonry Brush in an even layer working top to bottom with even, left to right strokes
- 3 Allow to dry 8 10 hours before applying 2nd coat

HELPFUL TIPS

- Test surface with water to check absorbency of masonry surface and mortar before applying. If water beads on surface you will need to apply Romabio MicroGrip Primer
- If temps are above 80°F, dampen the surface again before applying the 2nd coat to keep the surface cool
- For a flush, artistic finish or to smooth out highly recessed mortar joints, apply a pre-coat of Romabio Travertino plaster
- Extend the life of your finish with Romabio Mineral Shield. Learn more at romabio.com/mineralshield.





Scan to Learn More

^{*}For 1 coat based on average absorption. Actual coverage will vary based on surface texture, and absorption.

^{**}Lime Slurry comes Ready-To-Use. If desired, it can be diluted with clean water up to 5%. This chart represents the maximum dilution amounts.