



# CLASSICO LIMEWASH®

for DISTRESSED LIMEWASH ON BRICK AND STONE



Classico Limewash in Bianco White // Photo: Kindred Vintage

## PRODUCT FEATURES

- Authentic, Italian slaked lime paint used for beautiful, wash-off finishes on brick and stone
- No primer needed on absorbent, unpainted, unsealed natural masonry surfaces
- Easy to use, 1-coat paint process
- Breathable, long-lasting, and patinas over time
- Perfect for PROs and DIYers
- Ideal for Interior fireplaces
- Removable for the first 2 days for a no-stress application
- No odor, Zero-VOC, and environmentally friendly

“I have nothing against natural brick. I think it’s beautiful. But I am a sucker for that European lime washed brick.”

~ **Lauren Shaver, Bless'r House Blog**



# CLASSICO LIMEWASH

for DISTRESSED LIMEWASH ON BRICK AND STONE

## COLOR PROFILE & BASE TYPE

- Romabio offers seven curated whites and neutrals in the Classico Color Collection including Avorio White (neutral, off-white), Bianco White (pure, cool tone white), Cristallo White (antique, off-white), Nube Gray (subtle, beige-gray), Riposo Beige (light beige), Toscano Beige (soft beige), and Tropea Beige (true beige)
- Offered in White Base only that can be custom tinted light to medium-light colors
- Once dry, finish will be lighter and more opaque

## SIZES AVAILABLE

- **1L SKU:** CLW-BIANCO-WB-1L
- **2.5L SKU:** CLW-BIANCO-WB-2.5L
- **15L SKU:** CLW-BIANCO-WB-15L

## COVERAGE

- **1L/1 qt.** approximately 80 – 100 sq/ft\*
- **2.5L/.67 gal.** approximately 200 – 250 sq/ft\*
- **15L/4 gal.** approximately 1,200 – 1,500 sq/ft\*

*\*For 1 coat based on average absorption. Actual coverage will vary based on application method, surface texture, and absorption.*

## RECOMMENDED DILUTION

	1L/1QT	2.5L/0.67GAL	15L/4GAL
<b>50%</b>	500mL	1.25L	7.5L
<b>75%</b>	750mL	1.75L	11.25L
<b>100%</b>	1L	2.5L	15L

## APPLICATION ON BRICK or STONE

- 1** Dilute Classico Limewash 50% to a max of 100% with clean water and mix thoroughly before and during use.
- 2** Dampen the surface before painting for best results.
- 3** Apply with a Romabio Masonry Brush or an airless sprayer (min 3000psi and tip opening of 0.019"-0.021").
- 4** Distress the paint once it starts to dry (within about 30mins). Use a hose or spray bottle with a stiff stream for the most natural look. You can also use a wet cloth or soft brush depending on your desired finish.

Perform a full test of different dilutions and distressing techniques on the smallest wall first until you get the look you want before moving on to the rest of the project.

## HELPFUL TIPS

- Test surface with water to check absorption of masonry surface and mortar before applying. If water beads on surface, paint will not absorb properly.
- Paint complete wall from top to bottom to avoid lap lines.
- Only dilute the paint you will use within 5 days. Store remaining paint undiluted.
- Apply when temps are between 50°F and 88°F and avoid full sun if possible.
- Waterproof and extend the life of your finish with Romabio Mineral Shield. Learn more at [romabio.com/mineralshield](https://romabio.com/mineralshield).

### TOOLS



Scan to  
Learn More