

## DECORATIVE TOPCOAT FLAT

### Protective Coating for Romabio Decorative Paints & Plasters



#### PRODUCT FEATURES

- Polyurethane, water-based, clear finish
- Protects backsplashes and other high traffic vertical surfaces as well as horizontal surfaces with light foot traffic
- Designed for Romabio limewashes, mineral paints, and plasters
- Eco-friendly & Zero VOC
- Ideal for commercial applications
- Allows for easy cleaning of surfaces with mild detergent and water
- Non-Yellowing, fast-drying, excellent flow and adhesion

“My crew and I are huge fans of Romabio products, especially Velatura Mineralwash. Being able to protect our beautiful finishes in high traffic areas with Romabio Decorative Topcoat is a game changer for our high-end clients.”

~ **Tom Henman; Owner, Splat Paint**



# DECORATIVE TOPCOAT FLAT

## Protective Coating for Romabio Decorative Paints & Plasters

### COLOR & SHEEN PROFILE

- Clear coating that may make light colors slightly darker and dark colors slightly lighter
- Dead flat sheen; may slightly flatten the mottling or movement effect
- Test small area to check color and finish

### SIZES AVAILABLE

- 1L SKU: DTC-1L
- 2.5L SKU: DTC-2.5

### COVERAGE

- 1 Liter/1 Qt: approximately 130-150 sqft\*
- 2.5 Liter/0.67 Gal: approximately 325-375 sqft\*

*\*Actual coverage will vary depending upon application method, surface texture, and absorption. Test product on actual surface to determine accurate consumption.*

### RECOMMENDED DILUTION

*The product is ready to use. It is recommended to mix well before use. Only if necessary, the 2nd or 3rd coat can be diluted with a maximum of 10% water (1 part product to 1/10 part water)*

### APPLICATION ON INTERIOR VERTICAL SURFACES

- 1 **PREP** Surface must be clean, dry, compact and free of loose dirt or debris
- 2 **APPLY** 1st coat with a brush, roller or sprayer
- 3 **DRY** for at least 2 hours (fully cures in approx. 7 days)
- 4 **APPLY** 2nd coat if needed

### APPLICATION ON EXTERIOR OR HORIZONTAL SURFACES

- 5 **ADD** a 2nd or 3rd coat for added durability
- 6 **FOLLOW** the same steps above for the extra coat

### HELPFUL TIPS

- Touch-ups of original product are not possible after application of topcoat
- Must apply to full wall area – corner to corner
- Final color and effect may vary, test a small area before applying
- Surface must be clean and dry
- Not recommended for non-porous acrylic coatings or other non-porous surfaces
- Does not protect against boiling oil (recommend tile for those types of areas)

#### TOOLS



Scan to Learn More