



## MINERAL SHIELD

### PRODUCT FEATURES

Romabio Mineral Shield is an invisible coating that locks and protects beautiful Romabio mineral paint finishes from natural patina, or weathering created by water. The breathable coating repels water droplets but still allows water vapor to pass through, protecting the painted surface and preventing the growth of algae, moss, and mold. Unlike other products, Mineral Shield will not change the sheen of the finish or texture of the surface, thus preserving the beauty of a Romabio paint application. It also protects all lime-based coatings—such as Romabio Classico Limewash—from temporary discoloration that occurs when the surface is wet from rain and water absorption.

### PRODUCT USE

- Mineral Shield locks and protects the beauty of applications of Romabio Classico Limewash, Lime Slurry, Masonry Paints, and Marmorino Plasters
- Mineral Shield also protects uncoated porous brick, stone, stucco, concrete, or other masonry
- Not recommended for non-porous acrylic coatings or other non-porous surfaces
- Suitable for outdoor use and in any climatic or environmental conditions

### PRODUCT FEATURES

- **Prevents the growth** of algae, moss, and mold, keeping paint looking clean and fresh
- **Repels water**, reducing patina and extending the life of paint and ensuring a longer-lasting finish
- **Invisible coating** won't discolor exterior painted surfaces like other products
- **Significantly reduces staining** from clay, dirt and grass
- **Eco friendly**: safe for children, pets, and gardens
- **Biodegradable** and completely water-soluble
- **Easy to apply** with pump sprayer or brush

### COVERAGE

- Approximately 200-300 sq/ft per gallon with average absorption
- Actual coverage will vary depending upon application method, surface texture, and absorption
- Recommended to test product on actual surface to determine the exact consumption

### APPLICATION

1. Properly prepare and clean the surface for application. The surface should be clean, dry, and free from dirt and all loose particles
2. Ready to use. DO NOT DILUTE WITH WATER. Protect glass, wood surfaces, grass, and shrubbery from overspray. This product will not damage asphalt shingles
3. Can be applied with ordinary garden pump sprayer or brush. If applied with garden pump sprayer, eliminate most of the pressure at the spray nozzle and operate at the lowest pressure on the tank. The nozzle should be opened to a coarse spray adjustment. For even coating of material, start at the bottom of the wall and hold the spray at an angle to avoid splashing. It is important to hold the spray tip close to the surface to avoid run off. If applied with a brush, flow on liberally – do not brush out – to ensure even coating of the surface
4. If a second coat is applied, apply wet on wet within five minutes

**Application Temperature:** Apply in temperatures above 10°C / 50°F and below 35°C / 95°F.

