

LIME SLURRY

for a Textured Finish on Brick, Stone and Other Masonry



PRODUCT FEATURES

- Authentic, breathable, Italian lime paint used for beautiful, textured finishes in just 2 easy coats
- No primer needed on absorbent, unpainted, unsealed natural masonry surfaces
- Unique formulation allows Romabio Lime Slurry to harden like plaster
- For interior and exterior masonry surfaces
- Naturally mold-resistant and stands up to extreme temperatures
- No odor, Zero VOC and environmentally friendly

“It has amazing durability, but it’s so easy to use. It fills the mortar joints and crevices of the brick just like a plaster, but it is applied like a paint.

Another product offering from Romabio that we will be using much more in the future!”

~ *Hans Cook of Reflections of Italy*



LIME SLURRY

for a Textured Finish on Brick, Stone and Other Masonry

COLOR PROFILE & BASE TYPE

- Romabio offers seven curated whites and neutrals in the Classico Color Collection including Avorio White (neutral, offwhite), Bianco White (pure, cool tone white), Cristallo White (antique, off-white), Nube Gray (subtle, beige-gray), Riposo Beige (light beige), Toscano Beige (soft beige), and Tropea Beige (true beige)
- Offered in White Base only that can be custom tinted light to medium-light colors
- Once dry, finish will be lighter and more opaque

SIZES AVAILABLE

- **2.5L SKU: LSL-UNTINT-WB-2.5L**
- **15L SKU: LSL-UNTINT-WB-15L**

COVERAGE

- **2.5L/.67 gal.** approximately 90-100 sq/ft*
- **15L/4 gal.** approximately 540-600 sq/ft*

*For 1 coat based on average absorption. Actual coverage will vary based on surface texture, and absorption.

RECOMMENDED DILUTION**

	2.5L/.67GAL	15L/4GAL
5%	125mL	750mL


**Lime Slurry comes Ready-To-Use. If desired, it can be diluted with clean water up to 5%. This chart represents the maximum dilution amounts.

APPLICATION ON MASONRY

- 1 Dampen the surface to be painted and keep damp as needed, especially in high heat
- 2 Apply with a Romabio Masonry Brush in an even layer working top to bottom with even, left to right strokes
- 3 Allow to dry 8 – 10 hours before applying 2nd coat

HELPFUL TIPS

- Test surface with water to check absorbency of masonry surface and mortar before applying. If water beads on surface you will need to apply Romabio MicroGrip Primer
- If temps are above 80°F, dampen the surface again before applying the 2nd coat to keep the surface cool
- For a flush, artistic finish or to smooth out highly recessed mortar joints, apply a pre-coat of Romabio Travertino plaster
- Waterproof and extend the life of your finish with Romabio Mineral Shield. Learn more at romabio.com/mineralshield.



Scan to Learn More